



未注公差/General tolerances (mm)										0.05/10
0	>6	>18	>30	>50	>80	>120	>180	>250	<500	
~ 6	~ 18	~ 30	~ 50	~ 80	~ 120	~ 180	~ 250	~ 400	<500	
±0.10	±0.15	±0.20	±0.25	±0.30	±0.50	±0.80	±1.20	±1.50	±2.50	
										±1°

技术要求/Technical specification
标准/Standard: EN 175301-803(formerly DIN 43650)
接插孔位/Number of contacts: 2+PE
额定电压/Rated voltage: DC 12V, 24V
额定电流/Rated current: 10A
插拔次数/Durability: ≥50
防护等级/Protection class: IP65

序号/No.	描述/Description	数量/Qty	材质/Material	备注/Notes
10	密封框/Profiled gasket	1	NBR	黑色/Black
9	平垫片/Flat gasket	1	NBR	黑色/Black
8	接线座/Internal core	1	PA	黑色/Black
7	接线柱/Contact	3	铜/CuZn	镀锡/Tin plate
6	LED+电阻/LED+Resistor	1	/	红灯/Red
5	PG9螺母/PG9 cable gland	1	PP	黑色/Black
4	金属垫片/Grommet	1	碳钢/Carbon steel	镀锌/Zinc plate
3	O型圈/O-ring	1	NBR	黑色/Black
2	外壳/Housing	1	PC	透明/Transparent
1	安装螺钉/Fixing screw	1	碳钢/Carbon steel	镀锌/Zinc plate

备注/Remarks: ⑨, ⑩ 选择其中一款装配。 / Select one of them (⑨,⑩) to assemble.

电路图/Circuit diagram	平垫片/Flat gasket	密封框/Profiled gasket	螺钉/Screw M3X31

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO CIXI ZHONGTAI ELECTRIC APPLIANCE MANUFACTORY AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

CURRENT REV DESC:		慈溪市中泰电器厂 CIXI ZHONGTAI ELECTRIC APPLIANCE MANUFACTORY	
REVISION: A/0		2023/05/06	
DRWN: LU XD		2023/05/06	
CHKD: CHEN YY		2023/05/06	
APPR: CHEN G		2023/05/06	
产品描述/Description 电磁阀插头/SOLENOID VALVE CONNECTOR		产品编号/Comm.No. ZT-B-DC-PG9-T	
DIMENSION UNITS mm		SCALE 1:1	
THIRD ANGLE PROJECTION		DRAWING A3-SIZE	
SHEET NUMBER 1/1			